

**Product Data** 

## Hyspin<sup>™</sup> 4004

Hydraulic oil

## **Description**

Castrol Hyspin<sup>™</sup> 4004 (previously called Vitamol<sup>™</sup> 4004) is an hydraulic oil with distinctively efficient capabilities. The special additive combination improves the VI (Viscosity Index) performance, corrosion prevention, pressure absorption ability and the ageing protection.

## **Application**

The low viscosity Castrol Hyspin 4004, has a proven performance for use in shock absorbers. Furthermore, it is suited for all hydraulic systems, which need extremely precise control even with large variations in temperature. Possible applications are hydraulic elevators, hydraulics for water resource and distribution equipment, auxiliary engines, N/C controlled machine tools and copier hydraulics.

## **Typical Characteristics**

| Name                                | Method                | Units   | Hyspin 4004 |
|-------------------------------------|-----------------------|---------|-------------|
| Colour - Saybolt                    | ASTM D156 / ISO 2049  | Units   | 0.5         |
| Specific Gravity @ 15°C / 59°F      | ASTM D1298 / ISO 3675 | -       | 881         |
| Kinematic Viscosity @ 20°C / 68°F   | ASTM D445 / ISO 3104  | mm²/s   | 33          |
| Kinematic Viscosity @ 40°C / 104°F  | ASTM D445 / ISO 3104  | mm²/s   | 16.2        |
| Kinematic Viscosity @ 100°C / 212°F | ASTM D445 / ISO 3104  | mm²/s   | 4.4         |
| Viscosity Index                     | ASTM D2270 / ISO 2909 | -       | 202         |
| Pour Point                          | ASTM D97 / ISO 3016   | °C/°F   | -57         |
| Flash Point - open cup method       | ASTM D92 / ISO 2592   | °C/°F   | 134         |
| Acid Number                         | DIN 51558-1           | mgKOH/g | 2.8         |

Subject to usual manufacturing tolerances.

This product was previously called Vitamol 4004. The name was changed in 2015.

Hyspin™ 4004 05 Jul 2022

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

 $Castrol\ Industrial,\ Technology\ Centre\ ,\ Whitchurch\ Hill\ ,\ Pangbourne\ ,\ Reading\ ,\ RG8\ 7QR\ ,\ United\ Kingdom$ 

http://msdspds.castrol.com