



Variocut G 260

High performance neat cutting oil

Description

Castrol Variocut™ G 260 is a low viscosity neat cutting oil formulated without chlorinated paraffins.

Application

Variocut G 260 has been designed for honing and grinding of ferrous and non-ferrous materials. It can also be used for grinding applications, drilling and general machining of aluminium and yellow metals.

ü ü suggested core application ü possible application, please consult Castrol representative prior to use

	Cast Iron	Low-medium alloyed steel	High alloyed steel /nickelchromium alloys	Titanium alloys	Aluminium alloys	Yellow metals
Honing/Superfinishing	ü	ü	ü		ü	ü
Grinding	ü ü	ü ü	ü		ü ü	ü
Drilling	ü	ü			ü ü	ü
Broaching/Gear manufacturing						
General machining	ü ü	ü			ü ü	ü

Advantages

- Excellent flushing and lubrication properties help to extend honing stone life and enables high surface finish and dimensional accuracy
- Low viscosity and excellent wetting properties can reduce drag out and result in lower product usage
- Good filtering characteristics and high oxidation stability helps to increase product lifetime
- Formulated without chlorinated paraffins helps to improve the environmental profile and reduce disposal costs
- Low odour, light colour and low mist result in operator acceptability

Typical Characteristics

Name	Method	Units	Variocut G 260
Appearance	Visual	Visual	Yellow
Viscosity at 40°C	DIN 51562	mm ² /s	6.2
Density at 15°C	DIN 51757	g/cm ³	0.847
Flashpoint COC	ISO 2592	°C	128
Copper corrosion	ISO 2592	3 hr at 100°C	1a

Subject to usual manufacturing tolerances.

Storage

To avoid product deterioration always keep the container/drum tightly sealed. Store the product in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. For optimum product stability, it is preferable to store the product indoors between 5°C and 45 °C / 41°F and 113°F.

For more details, please refer the product safety data sheet.

Variocut G 260

08 Mar 2021

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

<http://msdspds.castrol.com>