



Tribol PM 320 S

Synthetic high-temperature circulation oil

Description

Tribol™ PM 320 S is a synthetic high-temperature oil with an extremely low evaporation rate. Designed for application in circulation lubricating systems. Due to the multi-grade characteristics Tribol PM guarantees trouble-free start-up of machines at low temperatures and reliable lubrication in the high-temperature range

Application

For use in circular systems operating at temperatures up to +140°C / 284°F - lubrication of sliding and rolling bearings, gears and other machine elements in large-scale equipment such as:

- Paper machines
- Calenders in the paper, textile and plastics industries
- Stirrers
- Rubber kneaders Rolling mills

Advantages

- Extremely thermally stable.
- Optimum wear protection.
- Utmost load carrying capacity.
- Excellent viscosity/temperature behavior.
- Extended service life.
- Excellent aging and oxidation stability and leaves no hard or carbon residues.
- Good corrosion protection.
- Good water separation.

Typical Characteristics

Name	Test Method	Units	Tribol PM 320 S
Colour	ASTM D1500	-	Yellow
Base oil	-	-	Synthetic oil
ISO Viscosity Grade	-	-	320
Density @ 15°C / 59°F	ASTM D4052 / ISO 12185	kg/m ³	914
Kinematic Viscosity @ 40°C / 104°F	ASTM D445 / ISO 3104	mm ² /s	319
Kinematic Viscosity @ 100°C / 212°F	ASTM D445 / ISO 3104	mm ² /s	36.3
Viscosity Index	ASTM D2270 / ISO 2909	-	162
Pour Point	ASTM D97 / ISO 3016	°C/°F	-30/-22
Copper corrosion (3 hrs@100°C/212°F)	ASTM D130 / ISO 2160	Rating	Pass
Flash Point - open cup method	ASTM D92 / ISO 2592	°C/°F	250/482

Subject to usual manufacturing tolerances.

Additional Information

- Compatible and miscible with mineral oils. Maximum performance, however, can be assured only if the product is not mixed with other lubricants.
- Compatible with all conventional sealing materials.

Tribol PM 320 S

17 Oct 2022

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

<http://msdspd.castrol.com>