



Calibration Oil C

Diesel injector calibration fluid

Description

Calibration Oil 'C' is a blend of specially selected and highly refined mineral oils and additives.

Application

Calibration Oil 'C' is recommended for use in certain diesel injector calibration equipment.

Typical Characteristics

Name	Method	Units	Calibration Oil C
Relative Density @ 20°C	g/ml	ISO 12185 / ASTM D4052	0.845
Viscosity @ 21°C	mm ² /s	ISO 3104 / ASTM D445	6.70
Flash Point, PMCC	°C	ISO 2719 / ASTM 93	126
Pour Point	°C	ISO 3016 / ASTM D97	-21

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Additional Information

Calibration Oil 'C' is manufactured to very close viscosity limits and is fully approved against Lucas CA70-10-100 specification.

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings.

Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Calibration Oil C

22 Dec 2011

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Marine, Technology Centre, Whitchurch Hill, Pangbourne, Reading RG8 7QR, United Kingdom

www.castrolmarine.com

