



Castrol Syntilo MR 81 BF

Synthetic Coolant

Description

Castrol Syntilo™ MR 81 BF is a mineral oil free synthetic coolant, which is formulated without boron and formaldehyde releasing agents. It forms a clear, stable solution in both hard and soft waters. Syntilo MR 81 BF exhibits good anti-corrosion properties coupled with excellent stability.

It can be used in both single sump machines as well as central systems.

Application

Castrol Syntilo MR 81 BF is recommended for surface, cylindrical, double disk and centerless grinding.

√√ suggested core application √ possible application, please consult Castrol representative prior to use

	Cast Iron	Low-medium alloyed steel	High alloyed - stainless steel	Aluminium alloys	Titanium alloys	Tungsten Carbide
Grinding	√√	√√	√			
Milling, Turning (General Machining)	√					
Drilling						
Reaming, Tapping						
Broaching						

Advantages

- Low foaming in all water conditions to ensure continuous grinding performance.
- Rejects tramp oil to the surface of the fluid for easy removal.
- Formulated without formaldehyde releasing agent and boron which help you to fulfil aspects of legislative requirements and waste treatment requirements that specify that these chemicals are excluded
- Settles chips quickly to prevent grinding wheel build-up and maintain a clean working environment.
- Resistant to mycobacteria as tested by an independent laboratory under standard test conditions.

Typical Characteristics

Name	Method	Units	
CONCENTRATION			
Appearance	Visual	-	Transparent, yellow
Density at 15°C	DIN 51757, ASTM D 1298	g/cm ³	1.12
Mineral Oil Content	Calculated	Vol %	0
SOLUTION			
Appearance	Visual	-	Transparent
pH (3%)	DIN 51361, ASTM E70-97	-	9.1
Factor Refractometer	-	-	1.5

Subject to usual manufacturing tolerances.

Recommended Concentrations

Grinding : 3 – 5%
Water range : 0 - 400 ppm CaCO₃

Storage

To avoid product deterioration always keep the container/drum tightly sealed. Store the product in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. For optimum product stability, it is preferable to store the product indoors between 5°C and 45 °C / 41°F and 113°F.

For more details, please refer the product safety data sheet.

Castrol Syntilo MR 81 BF

30 Mar 2021

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

<http://msdspds.castrol.com>